

The `jmsdelim` package

Jonathan Sterling

September 14, 2019

1 Overview

Sizing delimiters using `\left` and `\right` should be outlawed! The results are nearly always unaesthetic, primarily because the correct size of a mathematical delimiter is a typesetting consideration which does *not* emanate from the physical size of the interior.

Correctly sizing delimiters is very difficult, particularly in well-architected documents: a correctly engineered mathematical document will include macros for all operations, and these macros necessarily will include delimiters (such as parentheses). However, the correct size for the delimiter cannot be chosen ahead of time, because it will depend on the arguments; two options are available:

1. Provide optional arguments to each notation macro for choosing delimiter sizes.
This is nearly intractable to do in practice.
2. Ignore delimiter sizes.

With `jmsdelim` we offer an alternative: the correct delimiter sizes can be set at the *leaf nodes* of a mathematical expression, and magically bubble upward through the delimiters.

2 Document interface

`\DelimMin{<intexprmin>}`

This sets the minimum delimiter size to `<intexprmin>` outside the current location; delimiter sizes are represented as natural numbers, with 0 the smallest size.

`\DelimMin` is the work-horse of `jmsdelim`; let us consider an example of what one might do prior to adopting `jmsdelim`. Suppose we have defined a macro `\Psh` for the free completion, following the notation of the French school, and we wish to parenthesize an instance of it:

```
\NewDocumentCommand\Cat{}{\mathbf{Cat}}
\NewDocumentCommand\Psh{m}{\widehat{#1}}
\NewDocumentCommand\Hom{mmm}{
    \operatorname{Hom}_{-#1}(#2,#3)
}
\[\Hom{\Cat}{1}{\Psh{\mathbb{C}}}\]
```

One might have tried to get a better result by using `\left` and `\right`:

```
\NewDocumentCommand\Cat{}{\mathbf{Cat}}
\NewDocumentCommand\Psh{m}{\widehat{#1}}
\NewDocumentCommand\HomX{mmm}{
    \operatorname{Hom}_{#1}\left(\mathbf{Cat}, \widehat{\mathbf{C}}\right)
}
\NewDocumentCommand\Hom{mmm}{
    \operatorname{Hom}_{#1}\left(\mathbf{Cat}, \widehat{\mathbf{C}}\right)
}
\left[ \operatorname{Hom}_{\mathbf{Cat}}\left(1, \widehat{\mathbf{C}}\right) \right]
\left[ \operatorname{Hom}_{\mathbf{Cat}}\left(1, \widehat{\mathbf{C}}\right) \right]
```

The above is appallingly worse: the height of the hat does not in any way determine the correct size for the delimiter! The solution using `jmsdelim` is quite simple, however: first, we change `\Hom` to call `\DelimPrn`, and then we use `\DelimMin` within the `\Psh` notation.

```
\NewDocumentCommand\Cat{}{\mathbf{Cat}}
\NewDocumentCommand\Psh{m}{\operatorname{DelimMin}{1}\widehat{#1}}
\NewDocumentCommand\Hom{mmm}[
    \operatorname{Hom}_{#1}\left(\mathbf{Cat}, \widehat{\mathbf{C}}\right)
]
\left[ \operatorname{Hom}_{\mathbf{Cat}}\left(1, \widehat{\mathbf{C}}\right) \right]
```

Behavior under subscripts By default, delimiter sizes are capped under subscripts and superscripts because the alternative is unaesthetic. For instance, consider the following somewhat contrived examples:

```
\NewDocumentCommand\Sum{mm}{%
    \operatorname{DelimMin}{1}\textstyle\sum_{#1}^{#2}%
}
\left[ \operatorname{int}_{\operatorname{DelimPrn}{\operatorname{Sum}{i}}{a_i}} \right]
\left[ \operatorname{int}_{\operatorname{DelimPrn}{\operatorname{DelimMin}{4}}{\operatorname{Sum}{i}}{a_i}} \right]
```

Because the emitted delimiter size under a subscript does *not* determine the actual amount of space used, it is in most cases not correct for this delimiter size to have an effect on its non-subscript context. For this reason, judicious use of the `\DelimProtect` command is recommended in the case of subscripts.

2.1 Basic Delimiter commands

Like `mleftright` [Obel16], `jmsdelim` ensures the correct amount of space on the outside of the delimiters using `\mathopen` and `\mathclose`.

<code>\DelimSurround</code>	<code>\DelimSurround{\left\langle\right\rangle}{\left\langle\right\rangle}{\left\langle\right\rangle}</code> Surrounds <code>\left\langle body \right\rangle</code> with appropriately sized <code>\left\langle left \right\rangle</code> and <code>\left\langle right \right\rangle</code> delimiters respectively.
	$ \sum_i b_i $ <pre>\NewDocumentCommand\Sum{mm}% \DelimMin{1}{\textstyle\sum}_{#1}{#2}% } \[\DelimSurround{\left\langle\right\rangle}{\left\langle\right\rangle}{\left\langle\right\rangle}\]</pre>
<code>\DelimBetween</code>	<code>\DelimSurround{\left\langle sep \right\rangle}{\left\langle lbody \right\rangle}{\left\langle rbody \right\rangle}</code> Places an appropriately sized <code>\left\langle sep \right\rangle</code> between <code>\left\langle lbody \right\rangle</code> and <code>\left\langle rbody \right\rangle</code> .
	$a \parallel \sum_i b_i$ <pre>\NewDocumentCommand\Sum{mm}% \DelimMin{1}{\textstyle\sum}_{#1}{#2}% } \[\DelimBetween{\left\langle\right\rangle}{\left\langle a \right\rangle}{\left\langle b \right\rangle}\]</pre>
<code>\DelimBetweenSurround</code>	<code>\DelimSurround{\left\langle left \right\rangle}{\left\langle sep \right\rangle}{\left\langle right \right\rangle}{\left\langle lbody \right\rangle}{\left\langle rbody \right\rangle}</code> Places an appropriately sized <code>\left\langle sep \right\rangle</code> between <code>\left\langle lbody \right\rangle</code> and <code>\left\langle rbody \right\rangle</code> , surrounding the result by <code>\left\langle left \right\rangle</code> and <code>\left\langle right \right\rangle</code> respectively.
	$\left\{ \sum_i a \cdot b_i \mid a \in A \right\}$ <pre>\NewDocumentCommand\Sum{mm}% \DelimMin{1}{\textstyle\sum}_{#1}{#2}% } \left[\DelimBetweenSurround{\left\{ \right\}}{\left\langle\right\rangle}{\left\{ \right\}}{\left\langle lbrace \right\rangle}{\left\langle rbrace \right\rangle}% \left\{ \sum_i a \cdot b_i \mid a \in A \right\} \right]</pre>

\DelimProtect \DelimProtect{<body>}

Executes <body> in a sandbox, preventing its state updates from bubbling outward; this is useful in case of subscripts and superscripts. The following command demonstrates incorrect sizing in the presence of a high delimiter size within a subscript:

$$\left(\sum_{(\sum_i a_i)}^F \right)$$

```
\NewDocumentCommand\Sum{mm}{%
    \DelimMin{1}{\textstyle\sum}_{#1}{#2}%
}
\[%
\DelimPrn{\Sum{\DelimPrn{\DelimMin{4}{\sum{i}{a_i}}}{F}}%
\]
```

Using a combination of \DelimProtect and \DelimMin, the formatting can be corrected locally.

$$\left(\sum_{(\sum_i a_i)}^F \right)$$

```
\NewDocumentCommand\Sum{mm}{%
    \DelimMin{1}{\textstyle\sum}_{\DelimProtect{#1}{#2}}%
}
\[%
\DelimPrn{
    \DelimMin{2}{%
        \Sum{\DelimPrn{\DelimMin{4}{\sum{i}{a_i}}}{F}}%
    }%
\]
```

2.2 Derived delimiter commands

\DelimPrn \DelimPrn{<body>}

Surrounds <body> in parentheses.

\DelimBrk \DelimBrk{<body>}

Surrounds <body> in square brackets.

\DelimBrc \DelimBrc{<body>}

Surrounds <body> in curly braces.

\DelimGl \DelimGl{<body>}

Surrounds <body> in angle brackets.

\DelimVrt \DelimVrt{<body>}

Surrounds <body> in vertical brackets.

\DelimBbrk \DelimBbrk{<body>}

Surrounds <body> in Scott brackets (requires \llbracket, \rrbracket to be defined).

`\DelimVvrt` `\DelimVvrt{\langle body\rangle}`
Surrounds `\langle body\rangle` in double vertical bars.

2.3 Configuration and options

`\DelimSetup` `\DelimSetup{\langle options\rangle}`
`jmsdelim` can be customized along a few axes.

`size_commands` The option `size_commands` is a comma-separated list which contains a list of sizing commands for delimiters, from smallest to largest. By default, the standard `\big`, `\Big`, `\bigg`, `\Bigg` sequence is replaced by custom versions that behave differently in script size. This behavior can be overridden as follows:

```
\DelimSetup{  
    size_commands = {\relax,\big,\Big,\bigg,\Bigg}  
}
```

3 Interface for macro authors

The internals of `jmsdelim` are implemented in `expl3`.

`jmsdelim_scope:nn` `\jmsdelim_scope:nn {\langle pre\rangle} {\langle post\rangle}`

This is the fundamental control structure for authors of custom delimiting commands; `\langle pre\rangle` is a block of code that renders things to temporary boxes, and `\langle post\rangle` is code that *uses* these boxes, placing them relative to some delimiters. The function of `\jmsdelim_scope:nn` is to watch for the delimiter size updates induced by `\langle pre\rangle`, and set the delimiter size commands correctly before executing `\langle post\rangle`. Both `\langle pre\rangle` and `\langle post\rangle` are to be executed in the same block level.

`jmsdelim_hbox_set:Nn` `\jmsdelim_hbox_set:Nn {\langle box\rangle} {\langle contents\rangle}`

This command is meant to be used inside the `\langle pre\rangle` block of `\jmsdelim_scope:nn`; it typesets `\langle contents\rangle` in the box named by `\langle box\rangle`, correctly propagating the math style.

`jmsdelim_size_cmd:` `\jmsdelim_size_cmd:`

This command is meant to be used inside the `\langle post\rangle` block of `\jmsdelim_scope:nn` to set the size of a given delimiter; it behaves like `\big`, etc.

`jmsdelim_surround:nnn` `\jmsdelim_surround:nnn {\langle left\rangle} {\langle right\rangle} {\langle body\rangle}`

This routine surrounds `\langle body\rangle` with the delimiters `\langle left\rangle` and `\langle right\rangle` of the appropriate size respectively.

jmsdelim_between:nnn

jmsdelim_between:nnn {<sep>} {<lbody>} {<rbody>}

This routine separates $\langle lbody \rangle$ and $\langle rbody \rangle$ with a separator $\langle sep \rangle$ of the appropriate size.

jmsdelim_between:nnnnn

jmsdelim_between:nnnnn {<left>} {<sep>} {<right>} {<lbody>} {<rbody>}

This routine separates $\langle lbody \rangle$ and $\langle rbody \rangle$ with a separator $\langle sep \rangle$ of the appropriate size, and surrounds the result by $\langle left \rangle$ and $\langle right \rangle$ respectively of the same size.

jmsdelim_protect:n

jmsdelim_protect:n {<body>}

Executes $\langle body \rangle$ in a sandbox, preventing its state updates from bubbling upward.

4 jmsdelim implementation

```
1  {*package}
2  \RequirePackage{expl3}
3  \RequirePackage{l3keys2e}
4  \RequirePackage{xparse}
5  \RequirePackage{ifluatex}
6  \RequirePackage{scalerel}
7  \ProvidesExplPackage {jmsdelim} {2022/03/11} {0.2.0}
8  {Compositional delimiter sizing}
9  {@@=jmsdelim}
```

We first declare the options for the `jmsdelim` module, together with their default values.

```
10 \keys_define:nn { jmsdelim } {
11   size~commands .clist_set:N = \l__jmsdelim_size_cmds,
12 }
13 \keys_set:nn { jmsdelim } {
14   size~commands = {relax,jmsdelim_big:n,jmsdelim_Big:n,jmsdelim_bigg:n,jmsdelim_Bigg:n},
15 }
16
17 \cs_new:Npn \jmsdelim_big:n #1 {
18   {\mathchoice{\big #1}{\big #1}{\big #1}{#1}}
19 }
20
21 \cs_new:Npn \jmsdelim_Big:n #1 {
22   {\mathchoice{\Big #1}{\Big #1}{\Big #1}{#1}}
23 }
24
25 \cs_new:Npn \jmsdelim_bigg:n #1 {
26   {\mathchoice{\bigg #1}{\bigg #1}{\bigg #1}{#1}}
27 }
28
29 \cs_new:Npn \jmsdelim_Bigg:n #1 {
30   {\mathchoice{\Bigg #1}{\Bigg #1}{\Bigg #1}{#1}}
31 }
```

Then, we set up the internal state that will be used by `jmsdelim`.

```
32 \int_new:N \g__jmsdelim_size
```

```

33 \int_new:N \g__jmsdelim_size_up
34 \int_gset:Nn \g__jmsdelim_size {0}
35 \int_gset:Nn \g__jmsdelim_size_up {0}

```

4.1 Internals

`__jmsdelim_clist_item:Nn` A version of `\clist_item:Nn` that takes the last item when the index is out of bounds.

```

36 \cs_new:Npn \__jmsdelim_clist_item:Nn #1 #2 {
37   \clist_item:Nn #1 {
38     \int_min:nn {#2} {\clist_count:N #1}
39   }
40 }

```

(*End definition for `__jmsdelim_clist_item:Nn`.*)

`__jmsdelim_setup_sizes:`

```

41 \cs_new:Npn \__jmsdelim_setup_sizes: {
42   \int_gset:Nn \g__jmsdelim_size {
43     \int_max:nn \g__jmsdelim_size \g__jmsdelim_size_up
44   }
45
46   \cs_set_eq:Nc \jmsdelim_size_cmd: {
47     \__jmsdelim_clist_item:Nn \l__jmsdelim_size_cmds {
48       \g__jmsdelim_size + 1
49     }
50   }
51 }

```

(*End definition for `__jmsdelim_setup_sizes:..`*)

4.1.1 Preservation of math styles

It is fairly complicated and inefficient to preserve math styles across boxes. There is an appropriate way to do so in `LuaLATEX`, which we use conditionally if available; otherwise, we make use of `\ThisStyle` and `\SavedStyle` from `scalerel` [Seg16], which are more inefficient. In fact, it becomes impossible to use `jmsdelim` in `PDFLATEX` when the nesting is sufficiently deep, whereas there is no corresponding blowup in `LuaLATEX`. The `\ignoremode` and `\discernmode` macros from `scalerel` can be used to turn off the inefficient preservation of math styles locally, such as in the case where no subscripts are used.

```

\__jmsdelim_luatex_save_mathstyle:N
52 \cs_new:Npn \__jmsdelim_luatex_save_mathstyle:N #1 {
53   \ifcase \mathstyle
54     \cs_set_eq:NN #1 \displaystyle
55   \or
56     \cs_set_eq:NN #1 \crampeddisplaystyle
57   \or
58     \cs_set_eq:NN #1 \textstyle
59   \or

```

```

60      \cs_set_eq:NN #1 \crampedtextstyle
61  \or
62      \cs_set_eq:NN #1 \scriptstyle
63  \or
64      \cs_set_eq:NN #1 \crampedscriptstyle
65  \or
66      \cs_set_eq:NN #1 \scriptscriptstyle
67  \or
68      \cs_set_eq:NN #1 \crampedscriptscriptstyle
69  \fi
70 }

```

(End definition for __jmsdelim_luatex_save_mathstyle:N.)

--jmsdelim_restore_mathstyle:n

```

71 \cs_new:Npn __jmsdelim_restore_mathstyle: {
72     \SavedStyle
73 }

```

(End definition for __jmsdelim_restore_mathstyle:n.)

--jmsdelim_save_mathstyle:n

```

74 \cs_new:Npn __jmsdelim_save_mathstyle:n #1 {
75     \ifluatex
76         __jmsdelim_luatex_save_mathstyle:N __jmsdelim_restore_mathstyle:
77         #1
78     \else
79         \ThisStyle{#1}
80     \fi
81 }

```

(End definition for __jmsdelim_save_mathstyle:n.)

4.2 Public interface for macro authors

jmsdelim_scope:nn

```

82 \cs_new:Npn \jmsdelim_scope:nn #1 #2 {
83     \group_begin:
84         \int_set:Nn \l_tmpa_int \g__jmsdelim_size_up
85         \int_gset:Nn \g__jmsdelim_size_up 0
86         \int_gset:Nn \g__jmsdelim_size 0
87     \group_begin:
88         \__jmsdelim_save_mathstyle:n {
89             #1
90             \__jmsdelim_setup_sizes:
91             #2
92         }
93         \group_end:
94         \int_gset:Nn \g__jmsdelim_size_up {\int_max:nn \g__jmsdelim_size_up \l_tmpa_int}
95     \group_end:
96 }

```

(End definition for `jmsdelim_scope:nn`. This function is documented on page 5.)

`jmsdelim_hbox_set:Nn`

```
97 \cs_new:Npn \jmsdelim_hbox_set:Nn #1 #2 {
98   \mode_if_math:TF
99     { \hbox_set:Nn #1 {$\mathrel{\jmsdelim_restore_mathstyle: #2$} }
100    { \hbox_set:Nn #1 { #2 } }
101 }
```

(End definition for `jmsdelim_hbox_set:Nn`. This function is documented on page 5.)

`jmsdelim_surround:nnn`

```
102 \cs_new:Npn \jmsdelim_surround:nnn #1 #2 #3 {
103   \jmsdelim_scope:nn {
104     \jmsdelim_hbox_set:Nn \l_tmpa_box {#3}
105   }{
106     \mathopen\jmsdelim_size_cmd: {#1}
107     \box_use:N \l_tmpa_box
108     \mathclose\jmsdelim_size_cmd: {#2}
109   }
110 }
```

(End definition for `jmsdelim_surround:nnn`. This function is documented on page 5.)

`jmsdelim_protect:n`

```
111 \cs_new:Npn \jmsdelim_protect:n #1 {
112   \group_begin:
113   \int_set:Nn \l_tmpa_int \g_jmsdelim_size_up
114   \int_set:Nn \l_tmpb_int \g_jmsdelim_size
115   \group_begin: #1 \group_end:
116   \int_gset:Nn \g_jmsdelim_size_up \l_tmpa_int
117   \int_gset:Nn \g_jmsdelim_size \l_tmpb_int
118   \group_end:
119 }
```

(End definition for `jmsdelim_protect:n`. This function is documented on page 6.)

`jmsdelim_between:nnn`

```
120 \cs_new:Npn \jmsdelim_between:nnn #1 #2 #3 {
121   \jmsdelim_scope:nn {
122     \jmsdelim_hbox_set:Nn \l_tmpa_box {#2}
123     \jmsdelim_hbox_set:Nn \l_tmpb_box {#3}
124   }{
125     \box_use:N \l_tmpa_box
126     \mathrel{\jmsdelim_size_cmd: {#1}}
127     \box_use:N \l_tmpb_box
128   }
129 }
```

(End definition for `jmsdelim_between:nnn`. This function is documented on page 6.)

jmsdelim_between:nnnn

```
130 \cs_new:Npn \jmsdelim_between:nnnn #1 #2 #3 #4 #5 {
131   \jmsdelim_scope:nn {
132     \jmsdelim_hbox_set:Nn \l_tmpa_box {#4}
133     \jmsdelim_hbox_set:Nn \l_tmpb_box {#5}
134   }{
135     \mathopen\jmsdelim_size_cmd: {#1}
136     \box_use:N \l_tmpa_box
137     \mathrel{\jmsdelim_size_cmd: {#2}}
138     \box_use:N \l_tmpb_box
139     \mathclose\jmsdelim_size_cmd: {#3}
140   }
141 }
```

(End definition for `jmsdelim_between:nnnn`. This function is documented on page 6.)

4.3 Document interface

DelimMin

```
142 \NewDocumentCommand\DelimMin{m}){
143   \int_gset:Nn \g__jmsdelim_size_up {\int_max:nn \g__jmsdelim_size_up {#1}}
144 }
```

(End definition for `DelimMin`. This function is documented on page 1.)

DelimSurround

```
145 \NewDocumentCommand\DelimSurround{mmm} {
146   \jmsdelim_surround:nnn {#1} {#2} {#3}
147 }
```

(End definition for `DelimSurround`. This function is documented on page 3.)

DelimBetween

```
148 \NewDocumentCommand\DelimBetween{mmm}{%
149   \jmsdelim_between:nnn {#1} {#2} {#3}
150 }
```

(End definition for `DelimBetween`. This function is documented on page 3.)

DelimBetweenSurround

```
151 \NewDocumentCommand\DelimBetweenSurround{mmmm}{%
152   \jmsdelim_between:nnnn {#1} {#2} {#3} {#4} {#5}
153 }
```

(End definition for `DelimBetweenSurround`. This function is documented on page 3.)

DelimProtect

```
154 \NewDocumentCommand\DelimProtect{m}{  
155   \jmsdelim_protect:n {#1}  
156 }
```

(End definition for `DelimProtect`. This function is documented on page 4.)

DelimPrn

```
157 \NewDocumentCommand\DelimPrn{m}{  
158   \jmsdelim_surround:nnn {() ()} {#1}  
159 }
```

(End definition for `DelimPrn`. This function is documented on page 4.)

DelimBrk

```
160 \NewDocumentCommand\DelimBrk{m}{  
161   \jmsdelim_surround:nnn {[} {]} {#1}  
162 }
```

(End definition for `DelimBrk`. This function is documented on page 4.)

DelimBrc

```
163 \NewDocumentCommand\DelimBrc{m}{  
164   \jmsdelim_surround:nnn {\lbrace} {\rbrace} {#1}  
165 }
```

(End definition for `DelimBrc`. This function is documented on page 4.)

DelimBbrk

```
166 \NewDocumentCommand\DelimBbrk{m}{  
167   \jmsdelim_surround:nnn {\llbracket} {\rrbracket} {#1}  
168 }
```

(End definition for `DelimBbrk`. This function is documented on page 4.)

DelimGl

```
169 \NewDocumentCommand\DelimGl{m}{  
170   \jmsdelim_surround:nnn {\langle} {\rangle} {#1}  
171 }
```

(End definition for `DelimGl`. This function is documented on page 4.)

DelimVrt

```
172 \NewDocumentCommand\DelimVrt{m}{  
173   \jmsdelim_surround:nnn {\lvert} {\rvert} {#1}  
174 }
```

(End definition for `DelimVrt`. This function is documented on page 4.)

DelimVvrt

```
175 \NewDocumentCommand\DelimVvrt{m}{  
176   \jmsdelim_surround:nnn {\lVert} {\rVert} {#1}  
177 }
```

(End definition for `DelimVvrt`. This function is documented on page 5.)

```
178 \ProcessKeysPackageOptions {jmsdelim}
```

References

- [Obe16] Heiko Oberdiek. *The `mleftright` package*. May 16, 2016. URL: <https://ctan.org/pkg/mleftright> (cit. on p. 2).
- [Seg16] Steven B. Segletes. *scalerel – Constrained scaling and stretching of objects*. Dec. 29, 2016. URL: <https://ctan.org/pkg/scalerel> (cit. on p. 7).

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

B	
\Big	5, <u>22</u>
\big	5, <u>18</u> , 22, 26, 30
\Bigg	5, <u>30</u>
\bigg	5, <u>26</u>
box commands:	
\box_use:N	107, 125, 127, 136, 138
\l_tmpa_box	104, <u>107</u> , 122, 125, 132, 136
\l_tmpb_box	123, 127, <u>133</u> , 138
C	
clist commands:	
\clist_count:N	38
\clist_item:Nn	7, <u>37</u>
\crampeddisplaystyle	56
\crampedscriptscriptstyle	68
\crampedscriptstyle	64
\crampedtextstyle	60
cs commands:	
\cs_new:Npn	17, 21, 25, 29, 36, <u>41</u> , 52, 71, 74, 82, 97, 102, 111, 120, 130
\cs_set_eq:NN	<u>46</u> , 54, 56, 58, 60, 62, 64, 66, 68
D	
DelimBbrk	<u>166</u>
	\displaystyle

	E	
\else	78	
	F	
\fi	69, 80	
	G	
group commands:		
\group_begin:	83, 87, 112, 115	
\group_end:	93, 95, 115, 118	
	H	
hbox commands:		
\hbox_set:Nn	99, 100	
\Hom	2	
	I	
\ifcase	53	
\ifluatex	75	
\ignoremathstyle	7	
int commands:		
\int_gset:Nn		
.. 34, 35, 42, 85, 86, 94, 116, 117, 143		
\int_max:Nn	43, 94, 143	
\int_min:Nn	38	
\int_new:N	32, 33	
\int_set:Nn	84, 113, 114	
\l_tmpa_int	84, 94, 113, 116	
\l_tmpb_int	114, 117	
	J	
jmsdelim commands:		
\jmsdelim_between:nnn	120, 149	
\jmsdelim_between:nnn	6, 120	
\jmsdelim_between:nnnn	130, 152	
\jmsdelim_between:nnnnn	6, 130	
\jmsdelim_Big:n	21	
\jmsdelim_big:n	17	
\jmsdelim_Bigg:n	29	
\jmsdelim_bigg:n	25	
\jmsdelim_hbox_set:Nn		
..... 97, 104, 122, 123, 132, 133		
\jmsdelim_hbox_set:Nn	5, 97	
\jmsdelim_protect:n	111, 155	
\jmsdelim_protect:n	6, 111	
\jmsdelim_scope:nn	5, 82, 103, 121, 131	
\jmsdelim_scope:nn	5, 82	
\jmsdelim_size_cmd:		
..... 46, 106, 108, 126, 135, 137, 139		
\jmsdelim_size_cmd:	5	
\jmsdelim_surround:nn	102, 146, 158, 161, 164, 167, 170, 173, 176	
\jmsdelim_surround:nnn	5, 102	
jmsdelim internal commands:		
__jmsdelim_clist_item:Nn	36, 47	
	K	
keys commands:		
\keys_define:nn	10	
\keys_set:nn	13	
	L	
\langle	170	
\brace	164	
\left	1, 2	
\llbracket	4, 167	
\lVert	176	
\lvert	173	
	M	
\mathchoice	18, 22, 26, 30	
\mathclose	2, 108, 139	
\mathopen	2, 106, 135	
\mathrel	126, 137	
\mathstyle	53	
mode commands:		
\mode_if_math:TF	98	
	N	
\NewDocumentCommand	142, 145, 148, 151, 154, 157, 160, 163, 166, 169, 172, 175	
	O	
\or	55, 57, 59, 61, 63, 65, 67	
	P	
\ProcessKeysPackageOptions	178	
\ProvidesExplPackage	7	
\Psh	1, 2	
	R	
\rangle	170	
\rbrace	164	
\RequirePackage	2, 3, 4, 5, 6	
\right	1, 2	
\rrbracket	4, 167	
\rVert	176	

\rvert	173	T	
		S	
\SavedStyle	7, 72	\m@th	99
\scriptscriptstyle	66	\textstyle	58
\scriptstyle	62	\ThisStyle	7, 79
size_commands	5		